



PARAGON BUILDING PRODUCTS

PRODUCT INFORMATION ~ ITEM NO. 30304

Paragon Concrete Glue



PARAGON CONCRETE GLUE: is a re-emulsifiable liquid polymer emulsion used as an interior bonding agent.

FEATURES AND BENEFITS:

- Mold Resistant
- Resistant to Most Alkalis
- Re-wettable for continuous placement
- Bonds new concrete to old concrete

USES:

Interior Bonding Agent:

- | | |
|------------|----------------------------|
| • Plaster | • Acoustical Plaster |
| • Concrete | • Scratch & Brown Coat |
| • Masonry | • Cementitious Finish Coat |
| • Stucco | • Cementitious Base Coat |

Bonds to Interior Uncoated:

- | | |
|-----------|--------------------------|
| • Columns | • Concrete Blocks |
| • Beams | • Concrete Slabs |
| • Drywall | • Precast Concrete Walls |

PREPARATION: Evaluation of the substrate by a qualified engineer, architect or contractor is recommended. Clean area and remove all unsound concrete, grease, oil, paint, and any other foreign materials that will inhibit performance. Dampen porous substrates to improve penetration, coverage and bond strength.

Refer to:

- **ASTM D 4258** Surface Cleaning Concrete for Coating
- **ASTM D 4259** Abrading Concrete

PREPARATION (cont.):

- **ASTM D 4261** Surface Cleaning Unit Masonry for Coating
- **ICRI Guideline No. 03732** Selecting & Specifying Concrete Surface Preparation for Sealers, Coatings and Polymer Overlays

MIXING: Stir thoroughly

PLACEMENT: The Air, mix and Substrate temperatures should all be between 45° F (7° C) to 90° F (32.2° C).

Remove excess surface water and puddles prior to application of **Paragon Concrete Glue**.

Apply the interior plaster, concrete, cement paint, or stucco to the prepared surface while still tacky. Materials can be applied over the **Paragon Concrete Glue** within 7 days, as long as, the material will become tacky when dampened with water

CURING: Air cure the **Paragon Concrete Glue** for at least 20 minutes before applying materials.

PACKAGING:

1 Gallon (3.78 liters) plastic container 4 per case
5 Gallon (18.9 liters) pail

YIELD: One Gallon covers 250 ft² (23.2 M²) to 300 ft² (27.8 m²), depending upon the porosity and the texture of the substrate.

COLOR: White

SHELF LIFE: One year from date of manufacture.

PROTECT FROM FREEZING

DISPOSAL: Comply with all applicable local, state and federal regulations for disposal of unusable or contaminated materials. Dispose of packaging/containers according to local, state and federal regulations.



PARAGON BUILDING PRODUCTS

PRODUCT INFORMATION ITEM NO. 30304

Paragon Concrete Glue

LIMITATIONS:

- **DO NOT** allow to freeze
- **DO NOT** apply over wood
- **DO NOT** use below grade
- **DO NOT** use where it will be exposed to water
- **DO NOT** apply when air or substrate temperature is below 45°F (7.2° C) or above 90°F (32.2°C)

TECHNICAL SERVICE:

For, application procedures or surface conditions not specified in literature contact:

Paragon Concrete Products Inc.
2305 S Roof Tile Rd
Casa Grande, AZ 85193
Phone: 520-836-6454
Fax: 520-421-1172

Avoid hazards by following all precautions found in the **MSDS (Material Safety Data Sheet)**, product labels and product information sheets. Please read this information prior to using the product. **MSDS** are available through technical service at **520-836-6454**.

CAUTION: May cause allergic reactions.

Avoid eye contact or prolonged contact with skin. Use of a respirator, safety goggles and rubber gloves are recommended. Wash self thoroughly after any contact. In case of eye contact, flush immediately with plenty of water for at least 15 minutes. Consult a physician immediately.

KEEP OUT OF REACH OF CHILDREN

Avoid hazards by following all precautions found in the **MSDS (Material Safety Data Sheet)**, product labels and product information sheets. Please read this information prior to using the product.

LIMITED WARRANTY:

Paragon Building Products, Inc. (Paragon) warrants that this product and the materials used therein meet or exceed the applicable **ASTM** standards listed and in force at the time of manufacture. Paragon will replace any product or part which proves defective due to quality of

ingrredients used od due to the manufacturing process itself. This warranty shall apply only if the product is used in stict accordance to applicalbe specifications and instructions provided by Paragon for its use, and Paragon shall not be liable otherwise, Replacement of any defective product or, at Paragon's option, refund of the purchase price of any defective product shall be the buyers sole remedy under this warranty, and Paragon shall in no event be liable for any damages in excess of the purchase price of the defective product. **PARAGON SHALL IN NO EVENT BE LIABLE FOR ANY CONSEQUENTIAL INCIDENTAL OR SPECIAL DAMMAGES.**

This Warranty constitutes the sole warranty given by Paragon in connection with this product, and Paragon has authorized no person to make or give any other warranties or representations, oral or written on its behalf. **IN PARTICULAR, THERE ARE NO IMPLIED WARRANTIES, INCLUDING WITHOUT EXCEPTION WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** No modifications of this warranty in favor of any buyer shall be vaid unless given in writing and signed by an officer of Paragon.