



PARAGON BUILDING PRODUCTS

PRODUCT INFORMATION ITEM NO. 15660

KWIK-MIX CORE FILL GROUT



KWIK-MIX 80# CORE FILL GROUT:

Is a pre-mixed masonry grout that conforms to uniform building code 21-19, ASTM C-476 for core fill grout for structurally reinforced masonry, **Kwik-mix Core Fill Grout** is manufactured with Portland Cement, sand, and gravel.

FEATURES AND BENEFITS:

- ◆ Quality controlled
- ◆ Dry blended for maximum strength
- ◆ Consistent strengths bag to bag

USES:

KWIK-MIX Core Fill Grout is to be used when job site requirements are not conducive to mixer truck delivery, or small pours that are hard to schedule with ready-mix concrete, also when the distance from a batch plant does not allow concrete to be placed in the time frame of 1 ½ hours. The suggested uses for **KWIK-MIX Core Fill Grout** are structural concrete masonry units, structural hollow clay units, multi-wythe masonry structures and pilasters. Fine Grout is ideally suited for contractors with a mortar mixer at jobsites. Contractors need to batch a fine aggregate material to create a structural wall.

REQUIRED STRENGTHS:

	Days	ASTM C-476 Specifications	Kwikmix Grout
Fine Grout	28	2000 psi min.	3000 psi
Coarse Grout	28	2000 psi min.	3000 psi

MIXING:

To insure proper mixing place one gallon of water per 80 lb. bag in the mixer.

Installation:

Kwik-mix Core Fill Grout to a maximum 10" slump for best results, all the mixes are designed to maintain cohesion and not segregate at high fluidity. Place the mix either by pump or bucket, **DO NOT** pre-dampen the masonry to insure absorption of the water for convenience into the masonry unit. If placing in a pre-sealed block or brick, make sure prism test are performed prior to beginning the project.

CLEAN UP PROCESS:

Clean up is simple and easy with soap and water. Rinse tools before material hardens.

YIELD:

Each 80 lb bag will yield approximately .62 cubic feet at a 10 inch slump and 44, 80 lb bags produce approximately one cubic yard of wet material.

Masonry Units	Recommended	80 lb Bag per 100 sq. ft.
4"	Fine Grout	14
6"	Coarse/Fine	35
8"	Coarse	47
12"	Coarse	80

PACKAGING:

80 lb / 36.29 kg 42 per bag



PARAGON BUILDING PRODUCTS

PRODUCT INFORMATION ITEM NO. 15660

KWIK-MIX CORE FILL GROUT

LIMITATIONS:

- ◆ **DO NOT** apply when the air or substrate temperature is below 40° F within 24 hours
- ◆ **DO NOT** over water.
- ◆ **DO NOT** over mix.
- ◆ **DO NOT** apply over substrates that are frozen or contain frost.
- ◆ **DO NOT** use dirty water or tools.
- ◆ **DO NOT** add or mix any materials with this product unless approved by Paragon Concrete Products.

Application in cold or damp weather will increase the chance for the occurrence of efflorescence. Efflorescence occurs naturally and is beyond the control of Paragon.

TECHNICAL SERVICE: For, application procedures or surface conditions not specified in literature contact:

Paragon Aggregate Products
5420 W Bethany Home Rd.
Glendale, AZ 85301
Phone: 623-435-8271
Fax: 623-842-3929

Paragon Concrete Products Inc.
2305 S. Roof Tile Rd.
Casa Grande, AZ 85193
Phone: 520-836-6454
Fax: 520-421-1172

Avoid hazards by following all precautions found in the **SDS (Safety Data Sheet)**, product labels and product information sheets. Please read this information prior to using the product. MSDS are available through technical service at **520-836-6454**.

CAUTION: Contains Portland Cement. Cement causes skin Irritations, may cause allergic reactions. Avoid eye contact or prolonged contact with skin. Use of a dust respirator, safety goggles and rubber gloves are recommended. Wash self thoroughly after any contact. In case of eye contact, flush immediately with plenty of water

for at least 15 minutes. Consult a physician immediately. Do not take internally. Contains free silica, don't breathe dust. Prolonged exposure to dust may cause delayed lung disease (silicosis). Always wear NIOSH approved mask for silica dust.

LIMITED WARRANTY: Paragon Building Products, Inc. (Paragon) warrants that this product and the materials used therein meet or exceed the applicable ASTM standards listed and in force at the time of manufacture. Paragon will replace any product or part which proves defective due to quality of ingredients used or due to the manufacturing process itself. This warranty shall apply only if the product is used in strict accordance to applicable specifications and instructions provided by Paragon for its use, and Paragon shall not be liable otherwise. Replacement of any defective product or, at Paragon's option, refund of the purchase price of any defective product shall be the buyers sole remedy under this warranty and Paragon shall in no event be liable for any damages in excess of the purchase price of the defective product.

PARAGON SHALL IN NO EVENT BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL OR SPECIAL DAMAGES.

This Warranty constitutes the sole warranty given by Paragon in connection with this product, and Paragon has authorized no person to make or give any other warranties or representations, oral or written on its behalf. **In particular, there are no implied warranties, including without exception warranties of merchantability or fitness for a particular purpose.** No modifications of this warranty in favor of any buyer shall be valid unless given in writing and signed by an officer of Paragon.