

## **Safety Data Sheet**

**SECTION 1: PRODUCT IDENTIFICATION** 

## **Material Name:**

STONE VENEER MORTAR STONE VENEER MORTAR PLUS Grey and Brown

## Synonym:

## **Manufacturer Information:**

Paragon Aggregate Products, Inc. 2305 S Roof Tile Rd Casa Grande, AZ 85193 Phone: 520-836-6454 www.paragonbp.us

## **SECTION 2 – HAZARDS IDENTIFICATION**

## **GHS CLASSIFICTION:**

Acute Toxicity Oral – Category 4 Acute Toxicity Dermal – Category 4 Acute Toxicity Inhalation – Category 3 Skin Corrosion/Irritation – Category 1B Eye Damage – Category 1 Respiratory Sensitization – Category 1 Skin Sensitization – Category 1 Carcinogenicity – Category 1A Specific Target Organ Toxicity Repeat Exposure – Category 1

## GHS LABELS ELEMENTS:

## Symbols(s)



## **Signal Word**

Danger

## **Hazard Statements:**

Harmful if swallowed Harmful in contact with skin Toxic if inhaled Causes severe skin burns and eye damage Causes serious eye damage May cause allergy or asthma symptoms or breathing difficulties if inhaled May cause an allergic skin reaction May cause cancer Causes damage to organs through prolonged or repeated exposure (lungs)

## **Precautionary Statements:**

## **Prevention:**

Wash thoroughly after handling Do not eat, drink or smoke when using this product Wear protective gloves/protective clothing/eye protection/face protection Contaminated work clothing must not be allowed out of the workplace Obtain special instructions before use **Do Not** handle until all safety precautions have been read and understood **Do Not** breathe dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area In case of inadequate ventilation wear respiratory protection



## SECTION 2 – HAZARDS IDENTIFICATION (CONT.)

## **Precautionary Statements:**

## **Response:**

If swallowed: Rinse mouth, DO NOT induce vomiting. Immediately call a poison center/doctor.

If on skin (or hair: Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician. Wash contaminated clothing before reuse.

**If inhaled:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms, call a poison center or doctor/physician.

If in eye: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do, continue rinsing, immediately call a poison center/doctor.

#### Storage:

Store in a well-ventilated place

Store in an appropriate container or containment structure

#### **Disposal:**

Dispose of contents/container in accordance with local/regional/international regulations

#### **SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS**

#### **Chemical Name and Synonyms:**

Component	CAS #	Percent Optional
Cement, Portland Chemicals	65997-15-1	
Quartz	14808-60-7	
Iron Oxide Pigments	1317-61-9	

# Component Information/Information on Non-Hazardous Components General Product Information:

**Trace Elements:** Stone Veneer Mortar is made from materials mined from earth and is processed using energy provided by fuels. Trace amounts of naturally occurring, potentially harmful chemical might be detected during chemicals analysis. For example, Portland cement may contain up to 1.50% insoluble residue, some of which may be free crystalline silica. Other trace constituents may include calcium oxide, free magnesium oxide, potassium and sodium sulfate compounds, and trace metal compounds.

## **SECTION 4 – FIRST AID MEASURES**

## **First Aid Eyes:**

Immediately flush eye thoroughly with water. Continue flushing eye for a least 15 minutes, including under lids, to remove all particles. Call a physician immediately.

## **First Aid Skin:**

Wash skin with cool water and pH-neutral soap or mild detergent. Seek medical treatment if irritation or inflammation develops or persist. Seek medical treatment in the event of burns.

## **First Aid Inhalation:**

Remove person to fresh air. If breathing is difficult, administer oxygen. If not breathing, give artificial respiration. Seek medical help if coughing and other symptoms do subside. Inhalation of large amounts of Stone Veneer Mortar requires immediate medical attention.

## **First Aid Ingestion:**

Do not induce vomiting. If conscious, have the victim drink plenty of water and call physician.



## **SECTION 5 – FIRE FIGHTING MEASURES**

## **General Fire Hazards:**

See Section 9 for Flammability Properties Non combustible

## **Hazardous Combustion Products:**

NONE

## **Extinguishing Media:**

Use appropriate extinguishing media for surrounding fire

## **Unsuitable Extinguishing Media:**

NONE

## **Fire Fighting Equipment/Instructions:**

Firefighters should wear full protective gear

## **SECTION 6 – ACCIDENTAL RELEASE MEASURES**

## **Recovery and Neutralization:**

Stop the flow of material, if this is without risk

## **Personal Precautions, Protective Equipment and Emergency Procedures:**

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personal.

#### **Emergency Measures:**

Isolate area, keep unnecessary personal away

#### **Environmental Precautions:**

Do not attempt to wash Stone Veneer Mortar down sewers or storm drains

#### **Methods for Containment and Clean-up:**

Collect dry material using a scoop. Avoid actions that cause dust to become airborne. Avoid inhalation of dust and contact with skin. Scrape up wet material and place on an appropriate container. Allow the material to dry before disposal.

## **Prevention of Secondary Hazards:**

NONE

## **SECTION 7 – HANDLING AND STORAGE**

#### **Handling Procedures:**

Avoid prolonged or repeated breathing of dust. Avoid contact with eyes and skin. Promptly remove dusty clothing or clothing which is wet with cement fluids and launder before reuse. Wash thoroughly after exposure to dust or wet Stone Veneer Mortar.

## **Storage Procedures:**

Store product in a cool, dry, ventilated area. Protect against physical damage and moisture. Keep Stone Veneer Mortar dry until used. Normal temperature and pressures do not affect the material.

#### Incompatibilities:

Wet Stone Veneer Mortar is alkaline; as such it is incompatible with acids, ammonium salts and metal.



## **SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION**

#### **Component Exposure Limits:**

#### Cement, Portland, chemicals (65997-15-1)

ACGIH: 1m/m3 TWA (particulate matter containing no asbestos and<1% crystalline silica, respirable fraction) OSHA: 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)

NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)

#### Limestone (1317-65-3)

OSHA: 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)

## Gypsum (Ca(SO4).2H2O) (13397-24-5)

ACGIH: 10 mg/m3 TWA (inhalable fraction, listed under Calcium Sulfate) OSHA: 15 mg/m3 TWA (total dust); 5mg/m3 TWA (respirable fraction)

NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)

#### Quartz: (14808-60-7)

ACGIH: 0.25 mg/m3 TWA (respirable fraction) NIOSH: 0.05 mg/m3 TWA (respirable dust)

## **Engineering Measures:**

Periodically wash areas contacted by dry Stone Veneer Mortar or by wet cement or concrete fluids with a Ph neutral soap. Wash again at the end of work. If irritation occurs immediately wash affected areas and seek treatment. If clothing becomes saturated with wet concrete, it should be removed and replaced with clean clothing.

## **Personal Protective Equipment:**

#### **Respiratory:**

Use local or general ventilation to control exposures below applicable exposure limits, NIOSH or MSHA approved particulate filter respirators should be used in the context of respiratory protection program meeting the requirements of the OSHA respiratory protection standard [29 CFR 1910.134] to control exposures when ventilation or other controls are inadequate or discomfort or irritation is experienced. Respirator and/or filter cartridge selection should be based on American National Standards Institute (ANSI) Standards Z88.2 Practices for Respiratory Protection.

#### Hands:

Where prolonged exposure to unhardened mortar products might occur, wear impervious gloves to eliminate skin contact. Do not rely on barrier creams; barrier creams should not be used in place of gloves. Periodically wash areas contacted by Stone Veneer Mortar or its dry ingredients with pH neutral soap and water. Wash again at the end of the work. If irritation occurs, immediately wash the affected area and seek treatment.

## Eyes:

Where potentially subject to splashes or puffs of mortar, wear safety glasses with side shields or goggles. In extremely dusty environments and unpredictable environments wear unvented or indirectly vented goggles to avoid eye irritation or injury. Contact lenses should not be worn when working with Stone Veneer Mortar or fresh products.

#### Skin and Body:

Protection is essential to avoiding potentially severe skin injury. Avoid contact with unhardened Stone Veneer Mortar. If contact occurs, promptly wash affected area with soap and water. Where prolonged exposure to unhardened Stone Veneer Mortar products might occur, wear impervious clothing and gloves to eliminate skin contact. Wear sturdy boots that are impervious to water, to eliminate foot and ankle exposure.

## **SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

Appearance: Physical State: Vapor Pressure: Boiling Point: Solubility (H2O): Evaporation Rate: Octanol/H2O Coeff: Flash Point Method: Lower Flammability Limit (LFL): Auto Ignition: Gray Powder Solid Not Applicable Not Applicable Not Applicable Not Applicable None None None Odor: pH (in water): Vapor Density: Melting Point: Specific Gravity: VOC: Flash Point: Upper Flammability Limit (UFL): Burning Rate: None 12-13 Not applicable Not Applicable 3.15 Not Determined None None



## SECTION 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

#### **Chemical Stability:**

This is a stable material

#### Hazardous Reaction Potential:

Will not occur

## Conditions to Avoid:

Unintentional contact with water

#### **Incompatibility Products:**

Wet Stone Veneer Mortar is alkaline, As such it is incompatible with acids, ammonium salts and phosphorous

## Hazardous decomposition:

Will not spontaneously occur. Adding water produces (caustic) calcium hydroxide

## SECTION 11- TOXICOLOGICAL INFORMATION

#### Acute Toxicity: Component Analysis – LD50/LC50

**Quartz (14808-60-7)** Oral LD50 Rat 500 mg/kg

## **Potential Health Effects:**

#### Skin Corrosion Property/Stimulativeness

Discomfort or pain cannot be relied upon to alert a person to a hazardous skin exposure. Consequently, the only effective means of avoiding skin injury or illness involves minimizing skin contact, particularly contact with wet Stone Veneer Mortar. Exposed persons may not feel discomfort until hours after the exposure has ended and significant injury has occurred. Exposure during the handling or mixing of the dry ingredients in concrete mix may cause drying of the skin with consequent mild irritation or more significant effects attributable to aggravation of other conditions. Exposure to wet Stone Veneer Mortar may cause more skin effects including thickening, cracking or fissuring of the skin. Prolonged exposure can cause severe damage in the form of (caustic) chemical burn.

#### **Eye Critical Damage/Stimulativeness**

Exposure to airborne dust during the handling or mixing of the dry ingredients in Stone Veneer Mortar may cause immediate or delayed irritation or inflammation. Eye contact by splashes of wet Stone Veneer Mortar may cause effects ranging from moderate eye irritation to chemical burns and blindness. Such exposures require immediate first aid (see Section 4) and medical attention to prevent significant damage to the eye.

## Ingestion

Although inadvertent ingestion of small quantities of wet Stone Veneer Mortar or its dry ingredients are not known to be harmful, accidental ingestion of larger quantities can be harmful and requires immediate medical attention.

## Inhalation

Exposure to Stone Veneer Mortar in excess of the applicable TLV or PEL (see section 2) may cause or aggravate other lung conditions. The ingredients in Stone Veneer Mortar may contain trace amounts of crystalline silica. Exposure to these ingredients in excess of the applicable TLV or PEL (see Section 2) may cause or aggravate other lung conditions. Exposure to Stone Veneer Mortar may cause irritation to the moist mucous membranes of the nose, throat, and upper respiratory system. It may also leave unpleasant deposits in the nose.

#### **Respiratory Organs Sensitization/Skin Sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled, some individuals may exhibit an allergic response upon exposure to wet concrete. The response may appear in a variety of forms ranging from a mild rash to severe skin ulcers. Persons already sensitized mat react to their first contact with the product. Other persons may first experience this effect after years of contact with Stone Veneer Mortar products.



## SECTION 11- TOXICOLOGICAL INFORMATION CONT.

## **Generative Cell Mutagenicity**

This product is not reported to have any mutagenic effects

#### Carcinogenicity

#### **A: General Product Information**

May cause cancer: Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease and/or lung cancer! IARC states that crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1).

#### **B:** Component Carcinogenicity

· · · <b>I</b> · · · · · · ·	
ACGIH:	A4 – Not Classified as a Human Carcinogen
Quartz (14808-60-7)	
ACGIH:	A2 – Suspected Human Carcinogen
NIOSH:	potential occupational carcinogen
NTP:	Known Human Carcinogen (respirable size) (Select Carcinogen)
IARC:	Monograph 100C [2012] (listed under Crystalline silica inhaled in the form of quartz or
	cristobalite from occupational sources); Monograph 68 [1997] (Group 1 (carcinogenic to
	humans)

#### **Reproductive Toxicity**

This product is not reported to have any reproductive toxicity effects

## **Specified Target Organ General Toxicity:**

#### Single Exposure

This product is not reported to have any single exposure specific target organ toxicity effects

#### **Specified Target Organ General**

Causes damage to organs through prolonged or repeated exposure (lungs)

## **Aspiration Respiratory Organs Hazard**

This product is not reported to have any aspiration hazards

## **SECTION 12 – ECOLOGICAL INFORMATION**

## **Ecotoxicity**

#### **A: General Product Information**

This product is not reported to have any ecotoxicity effects

#### **B:** Component Analysis – Ecotoxicity – Aquatic Toxicity

No ecotoxicity data are available for this product's components

#### Persistence/Degradability

No information available for the product

#### **Bioaccumulation**

No information available for the product

#### Mobility in Soil

No information available for the product

## SECTION 13 – DISPOSAL CONSIDERATIONS

#### **Waste Disposal Instructions**

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations

## **Disposal of Contaminated Containers or Packaging**

Dispose information available for the product

#### **SECTION 14 – TRANSPORTATION INFORMATION**

## **DOT Information**

## Hazardous materials description proper shipping name:

Hazard Class	Not applicable
Identification number	**
Required label text	11
Hazardous substance / reportable quantities (RO)	11



## **SECTION 15 – REGULATORY INFORMATION**

#### **Regulatory Information**

**US Federal Regulations** 

#### **Component Analysis**

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A). SARS Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4)

#### **State Regulations**

#### **Component Analysis – State**

The following components appear on one or more of the following state hazardous substances lists;

Components	CAS	CA	MA	MN	NJ	PA	RI
Cement, Portland, Chemicals	65997-15-1	No	Yes	Yes	Yes	Yes	No
Quartz	1408-60-7	No	Yes	Yes	Yes	Yes	No
Iron Oxide Pigments	1317-61-9						

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

## Component Analysis – WHMIS IDL

No components are listed in the WHMIS IDL Additional Regulatory Information

## **Component Analysis – Inventory**

Component	CAS #	TSCA	CAN	EEC
Cement, Portland. Chemicals	65997-15-1	Yes	DSL	EINECS
Quartz	14808-60-7	Yes	DSL	EINECS
Iron Oxide Pigments	1317-61-9			



## **SECTION 16 – OTHER INFORMATION**

Hazardous Material Information System (HMIS):	Health	1
	Flammability	0
	Physical Hazard	0
	Personal Protection	В

## Revision: April 2015 Prepared by; R. Radel / A. Gallegos

### **NFPA/HMIS Definitions:**

0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

## **Protective Equipment:**

Safety glasses, gloves

## Key/Legend

EPA = Environmental Protection Agency

TSCA = Toxic Substance Control Act

ACGIH = American Conference of Governmental Industrial Hygienists

IARC = International Agency for Research on Cancer

NIOSH = National Institute for Occupational Safety and Health

NTP = National Toxicology Program

OSHA = Occupational Safety and Health Administration

NJTSR = New Jersey Trade Secret Registry

## Literature Reference

None

## **Other Information**

NOTE: SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OT FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY PARAGON CONCRETE PRODUCTS, except the product shall conform to contracted specifications. The information provided herein was believed by Paragon Concrete Products Inc. to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as to product delivered or for non-delivery of product, and whether based on contract, breach of warranty, negligence , or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.

\*NOTE: Since other Agencies regulate this information, OSHA will not be enforcing SECTIONS 12 through 15 (29 CFR 1910.1200 (g) (2)).