

BLACKTOP & ASPHALT PATCH



PARAGON BLACKTOP & ASPHALT PATCH is a blended mixture of slow cure liquid asphalt (SC800) meeting the ASTM D-2026 specifications; and aggregate composition and grading meeting Standard Specifications for Public Works Construction 1988 for Class D2 Asphalt Concrete.

FEATURES AND BENEFITS:

- ◆ Ready to use
- ◆ For applications of 2-4 inches in thickness
- ◆ Can be opened to traffic immediately after compacting

USES:

Repairing of

- ◆ Potholes
- ◆ Cracks over 1 inch wide

YIELD:

60 lbs. (27.2 kg) = approximately .40 ft³ (.01 m³)

PREPARATION:

Remove all loose and broken blacktop. Square cut the vertical sides to provide proper confinement of the patch. Check for soundness of sub-base. If unsound remove and replace with clean mixture of sand and gravel. Compact with a tamper. Sweep area ensuring no dirt or loose particles near area to be patched.

PLACEMENT:

- ◆ Place tack coat of Paragon Asphalt Glue on all vertical edges.
- ◆ Pour a 2 inch layer of Blacktop & Asphalt Patch into area to be patched.
- ◆ Level and compact with a tamper.
- ◆ Add more Blacktop & Asphalt Patch and tamp until patch is 1/2" thicker than surrounding area.

CURING:

Paragon Blacktop & Asphalt Patch is ready for traffic immediately after satisfactorily leveling and compact. To avoid tracking of the asphalt emulsion a light coating of sand over the patch will help. Don't apply any sealer to the area that was patched for a period of 60-90 days.

PACKAGING:

60 lbs. / 27.2 kg plastic bags 50/Pallet

LIMITATIONS:

- ◆ **DO NOT** use in unconfined areas such as curbs, speed bumps, ramps or driveways
- ◆ **DO NOT** apply in lifts thicker than one inch after compacting
- ◆ **DO NOT** apply driveway sealers before 90 days
- ◆ **DO NOT** allow dry turning of tires for 24 hours
- ◆ **DO NOT** apply over substrates that are frozen or contain frost

TECHNICAL SERVICE:

For application procedures or surface conditions not specified in literature contact:

Paragon Building Products Inc.

2895 Hamner Avenue
Norco, CA 92860
Phone: 951-549-1155
Fax: 951-549-1177

Avoid hazards by following all precautions found in the MSDS (Material Safety Data Sheet), product labels and product information sheets. Please read this information prior to



CONTINUED

using the product. MSDS are available through technical service at 951-549-1155.

LIMITED WARRANTY:

Paragon Building Products, Inc. (Paragon) warrants that this product and the materials used therein meet or exceed the applicable ASTM standards listed and in force at the time of manufacture. Paragon will replace any product or part which proves defective due to quality of ingredients used or due to the manufacturing process itself. This warranty shall apply only if the product is used in strict accordance to applicable specifications and instructions provided by Paragon for its use, and Paragon shall not be liable otherwise. Replacement of any defective product or, at Paragon's option, refund of the purchase price of any defective product shall be the buyer's sole remedy under this warranty, and Paragon shall in no event be liable for any damages in excess of the purchase price of the defective product. **PARAGON SHALL IN NO EVENT BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL OR SPECIAL DAMAGES.**

This Warranty constitutes the sole warranty given by Paragon in connection with this product, and Paragon has authorized no person to make or give any other warranties or representations, oral or written on its behalf. **In particular, there are no implied warranties, including without exception warranties of merchantability or fitness for a particular purpose.** No modifications of this warranty in favor of any buyer shall be valid unless given in writing and signed by an officer of Paragon.